TECHNICAL DATA SHEET

Issue Date: 01.05.2026 **Revision: 01**

Product Information



Name	**Zebo ZB444 Floor Paint – Hybrid Acrylic Resine Based 1K**
Code	ZEBO.ZB444
Description	A ready-to-use, water-based decorative floor paint based on a hybrid acrylic copolymer emulsion. It offers high abrasion resistance, strong adhesion, water repellency and UV resistance, and is suitable for light- to medium-duty traffic.
Color:	Available colors
Packaging:	3.5 kg – 20 kg metal bucket

Area of Uses

- Horizontal and vertical surfaces, indoors and outdoors.
- Factory and warehouse floors used by forklifts and pallet trucks.
- High-pedestrian-traffic areas such as shopping centres, shops and supermarkets.
- Concrete pavements, sidewalks, paving stones and car parks.
- Cycle lanes, walking tracks and parks.

Properties

- Ready to use and easy to apply.
- High UV resistance.
- Fast drying saves time.
- Excellent hiding power.
- Extra resistance to abrasion.
- High adhesion strength.
- Suitable for light- and medium-duty traffic (forklifts, pallet trucks and pedestrians, etc.).
- Prevents surface dusting.
- Excellent water repellency.
- Improved resistance to soiling and easy cleaning.
- Suitable for all horizontal and vertical surfaces.
- High resistance to standing water.

Application Precautions

- Ambient temperature must be between +5 °C and +35 °C.
- Do not apply to frozen or thawing surfaces, or where frost is expected within 24 hours.
- Do not apply in direct sunlight, strong winds or extreme heat.
- Do not apply in rainy weather. Protect the coated surface from drafts and rain for 24 hour

Yıltic Yıldırım Yapı Malzemeleri İnş.San. ve Tic. Ltd.Şti.
Yapımaks Yapı Market

Address: Kuruçay Mh. D-100 Karayolu Cd. No: 253
Merkez/Bolu TÜRKİYE
Telephone: +90 374 245 15 00
e-mail:info@yiltic.com

This product is manufactured at Albera facilities certified to TS EN ISO 9001:2015 and TS EN ISO 14001:2015.

The manufacturer and supplier are not responsible for application errors caused by failure to follow instructions or use outside the intended purpose. The companies reserve the right to modify products without prior notice in line with technological developments.

Application Limits

(at 21±2 °C and 50±5% relative humidity)

Number of coats:	At least 2 coats
Recoat interval:	At least 6 hours
Full drying time:	At least 24 hours
Ready to pedestrian traffic:	At least 24 hours
Ready for vehicle traffic:	At least 7 days

Application

- The substrate must be clean, dry and sound. Remove cement laitance, oil and grease using a high-pressure water jet. Scrape off and completely remove plaster residues and similar deposits.
- Completely remove any form-release oil, dust, paint or similar contaminants from the surface.
- If repairs or filling are required, use Darkss QF-666 Repair Mortar.
- Check the substrate with a hammer to identify weak areas. Remove unsound sections and leave square-cut edges around the areas to be repaired.
- Form fillets at all junctions between horizontal and vertical surfaces.
- After cleaning, apply one coat of Darkss Primast 200 Primer to improve adhesion and regulate substrate absorbency. Allow to dry for 2–3 hours.
- Provide a slope towards drains on horizontal surfaces to prevent water accumulation.
- Zebo Floor Paint is ready to use. Before application, mix in its original container at 400–500 rpm until homogeneous and free of lumps. Apply at least two coats to the prepared surface by brush, roller or spray. Allow at least 6 hours between coats and apply successive coats in perpendicular directions.
- Keep the container closed during application breaks to prevent skin formation.
- Do not use against negative-side hydrostatic pressure.
- Protect the surface from drafts and water contact during and after application.
- Do not add any foreign materials during application.
- Clean all tools thoroughly with plenty of water before the product dries.

Consumption

- For roller or brush application, 1 litre covers 5–6 m² in one coat or 3–4 m² in two coats, depending on substrate type, absorbency and ambient conditions (excluding spills and losses).
- For spray application, 1 litre covers 4–5 m² in one coat or 2.5–3.5 m² in two coats, depending on substrate type, absorbency and ambient conditions (excluding spills and losses).
- Coverage may vary with substrate and ambient conditions. Carry out a controlled trial to determine actual consumption.

Yıltic Yıldırım Yapı Malzemeleri İnş.San. ve Tic. Ltd.Şti.
Yapımaks Yapı Market

Address: Kuruçay Mh. D-100 Karayolu Cd. No: 253
Merkez/Bolu TÜRKİYE
Telephone: +90 374 245 15 00
e-mail:info@yiltic.com

This product is manufactured at Albera facilities certified to TS EN ISO 9001:2015 and TS EN ISO 14001:2015.

The manufacturer and supplier are not responsible for application errors caused by failure to follow instructions or use outside the intended purpose. The companies reserve the right to modify products without prior notice in line with technological developments.

Safety Precautions

- Read the **Technical Data Sheet** before use.
- May cause allergic reactions.
- Avoid inhalation and contact with the body
- Do not eat or swallow.
- Keep away from foodstuffs.
- Keep out of reach of children.
- Wear gloves, safety goggles and a mask during work.
- Mix in a well-ventilated area.
- In case of contact with eyes or skin, rinse with plenty of water and seek medical advice.
- Wash hands thoroughly with water after application.
- Do not discharge into water supply systems or sewers.
- Hazard and Precautionary Statements: H318; H335; P264; P261; P272; P271; P302+P352; P363

Storage and Shelf Life

- Store between +5 °C and +35 °C in a dry, moisture-free environment (maximum 60% relative humidity), away from direct sunlight.
- Keep containers tightly closed when not in use.
- Protect the product from freezing.
- Do not stack pallets on top of one another during storage or transport.
- Shelf life is up to 12 months from the date of manufacture when stored under the specified conditions.

Yıltic Yıldırım Yapı Malzemeleri İnş.San. ve Tic. Ltd.Şti.
Yapımaks Yapı Market

Address: Kuruçay Mh. D-100 Karayolu Cd. No: 253
Merkez/Bolu TÜRKİYE
Telephone: +90 374 245 15 00
e-mail:info@yiltic.com

This product is manufactured at Albera facilities certified to TS EN ISO 9001:2015 and TS EN ISO 14001:2015.

The manufacturer and supplier are not responsible for application errors caused by failure to follow instructions or use outside the intended purpose. The companies reserve the right to modify products without prior notice in line with technological developments.